

ARTIC DRIERS™

International (Pty) Ltd

Compressed Air Downstream Equipment and Accessories

Artic 22 Automatic Drain Valve

The Artic 22-2 Timer Controlled Condensate Drain combines the solenoid valve and an electronic timer. It is specifically designed to automatically remove condensate from compressed air systems. The Artic 22-2 removes condensate from compressors, compressed air dryers, inline filters airlines and receivers up to any size, of any type or manufacturer. Turbo air compressors excluded.

The Artic 22-2 offers simple installation and is recognised as a most reliable and great performing condensate drain. The large orifice in the direct acting valve, combined with its quality timer module provides reliable trouble-free draining of condensate, providing minimum service work is carried out.



PRESSURE RANGE	0 - 16 bar (40+ bar version available)
MAXIMUM COMPRESSOR CAPACITY	Unlimited
SUPPLY VOLTAGE OPTIONS	12 - 220 VAC/DC 50/60Hz. Please specify on your order
MEDIUM TEMPERATURE	1 - 55 °C
AMBIENT TEMPERATURE	1 - 55 °C
TIMER CYCLE RANGE (ON / OFF)	0.5 - 10 seconds / 0.5 - 45 minutes
TIMER PCB	High technology, Pick and place ensures quality
TEST BUTTON	Yes
TIMER CYCLE INDICATION	Bright LED illumination
VALVE TYPE	2/2 way, direct acting
VALVE ORIFICE	4.0 mm
VALVE SEALS	FPM
INLET/OUTLET CONNECTIONS	1/2" BSP
SERVICEABLE VALVE	Yes
VALVE HOUSING MATERIAL	Brass
POWER CONNECTION	DIN 43650-A
ENVIRONMENTAL PROTECTION	IP65 (NEMA4)